

## AIR HOSE XA20

Oil mist resistant air hose for versatile general industries and construction sites.  
NOT suitable for transfer of petroleum products.



**Tube:** Black, smooth, NR/SBR Blended

**Reinforcement:** High strength synthetic yarn

**Cover:** Black/Yellow, smooth, SBR/EPDM Blended (Smooth/Fluted)

**Temperature:** -20°C ~ +80°C

**Safety Factor:** 3:1

**Standard Length:** 50/100m (Other lengths available upon request)

**Branding:** EUROMAX XA20 AIR HOSE 20 BAR WP

(Blue wordings)

PRODUCT CODE	NOMINAL (inch)	I.D. (mm)	O.D. (mm)	W.P.		B.P.		Weight kg/m
				(bar)	(psi)	(bar)	(psi)	
XA 0140	1/4"	6.4	13.0	20	300	60	900	0.169
XA 0516	5/16"	7.9	15.0	20	300	60	900	0.215
XA 0380	3/8"	9.5	17.0	20	300	60	900	0.263
XA 0120	1/2"	12.7	21.0	20	300	60	900	0.370
XA 0580	5/8"	15.9	26.0	20	300	60	900	0.560
XA 0340	3/4"	19.1	29.0	20	300	60	900	0.630
XA 0780	7/8"	22.2	32.5	20	300	60	900	0.746
XA 1000	1"	25.4	36.0	20	300	60	900	0.856
XA 1140	1-1/4"	31.8	44.0	20	300	60	900	1.217
XA 1120	1-1/2"	38.1	54.0	20	300	60	900	1.927
XA 2000	2"	50.8	66.0	20	300	60	900	2.336

Note: Higher pressure available upon request.